

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



(19)

(11) Publication number:

**58074180 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **56173354**(51) Intl. Cl.: **C02F 1/24**(22) Application date: **28.10.81**

(30) Priority:	(71) Applicant: <b>mitsui miike mach co ltd</b> <b>sanwa eng:kk</b>
(43) Date of application publication: <b>04.05.83</b>	(72) Inventor: <b>MIWA SATORU</b>
(84) Designated contracting states:	(74) Representative:

**(54) FROTH SCRAPER****(57) Abstract:**

**PURPOSE:** To permit effective scraping without disturbing froth at all by providing a froth scraping mechanism and a moving base having a conveyor along a flotation condensing tank.

**CONSTITUTION:** A driving source 12 for a scraping plate and a driving source 13 for a conveyor are installed on the frame 11 of a moving base 10. A froth scraping mechanism 20 gives circular motion to a swiveling mechanism S, a scraping plate 22, a tail rod 23 and a scraping plate 22. The plate 22 is of a slender flat plate shape and is formed with a slender barlike part 22a in the end part thereof. A mechanism that gives circular motion is connected to the part 22a. For example, a crank plate 21 is supported freely rotatably to the base 10 and is driven by the driving source 12 of the plate 21. A crank pin 21a is provided on the radial circumference from the center O of the plate 21. The pin 21a supports the part 22a freely turnably.

